SAN2130NABAW

1.3 MEGAPIXEL HIGH RESOLUTION IP CAMERA

Key Features

- 1/3" CMOS
- 1.3 Megapixel
- Automatic White Balance
- 4mm Lens
- H.264 Video Compression
- Audio Communication
- IP66 Standard

Image Sensor	1/3" CMOS
Video Processing	• H.264 Video encoding, support for dual-stream • AVI Format • Support stream 0.1M ~ 6Mpbs adjustable • Support Frame rate 1 to 25 frames / sec adjustable
Lens	4 mm
IR Distance	Upto 30 Meters
Image output	Main stream: 1280*960@25fps; Sub-stream:640*360,352*288
Synchronous mode	IR-CUT Driver Interface；Support photoresistor input signal and IR-CUT, IR light linkage
Network Interface	• RJ45 Ethernet Interface, • 10/100M Adaptive; • Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
Color Style	Color / B & W / manual / external
Business function	• Support WEB configuration, • Support OSD • Supports real-time video transmission, • Support motion detection, • Support alerts and screen pop-linkage after motion detection alarm, • Support JPEG capture, • Support unified client remote monitoring software, • Support cloud services, • Large platform system applications, • Provide comprehensive SDK development kit
Audio	Supports audio Communication
Input voltage	DC10V
Phone supports	Cell Phone Monitoring (iPhone, Windows Mobile, Android)
BLC	Auto / Manual
Dynamic Range	42dB
Power	DC12V═1.2w
Minimum illumination	Color 0.1Lux@F1.2；B & W 0.01 Lux@F1.2(O Lux LED ON)
Wide voltage and low current	Yes
Image Algorithm	Standard H.264 video compression algorithm
Lightning Protection	Yes
Operating Temperature	-10°C～+45°C
Storage Temperature	-40°C～+80°C
Storage Humidity	Relative Humidity 85% (without condensation)

ONVIF

Headquater: 401, Block G, 8# buliding, shangxue Industrial North Area, Bantian, Longgang District,Shenzhen, China
Email: care@santachi.net Web: www.santachi.net

Santachi® inspire the future
www.santachi.net