SAN3313OSDA

36X ZOOM, 1.3 MP AHD MINI HIGH SPEED DOME CAMERA

Key Features

- 1/3" CMOS 1.3 Mega Pixel AHD
- Resolution 960P
- Rotate 360°in horizontal direction
- Vertical 90° continuous monitoring after auto reversing 180°
- Adjustable rotation speed according to the zoom rate
- Built in OSD
- Pelco-D and Pelco-P are compatible and Baud rate is adjustable
- IP66 Standard Weatherproof

Image Sensor	1/3" 1.3 Mega Pixel CMOS AHD
Electronic Shutter	PAL:1/50~1/10000 NTSC:1/60~1/12000
Sync. System	Internal / Line Lock
TV System	PAL/NTSC
Effective Pixel	PAL:1280(H) ×960(V) NTSC:1280(H) ×960(V)
S/N Ratio	>50dB
Horizontal Resolution	960P
Backlight Compensation	On/Off
Min. Illumination	Color:0.01Lux Black:0.001Lux
White Balance	Auto
Focus Length	5~90mm
Optical Focus	36x
Focus	Auto/Manual/Auto zoom
Presets	255
Patrol Track	4 Groups
Cruise Track	4 Groups, each can add 16 presets
IR distance	Up to 80 Mtr.
Horizontal Range	360°Unlimited rotation
Vertical Range	-90°-0°
Manual Speed	0.01°-180°/s
Protocol	PELCO D and PELCO P
Preset Call Speed	Max 200°/s
IR life	30000 hours
Function	AB scan, patrol track, guard position, ratio zoom, timing function, dome camera's title
IR light angle	Infrared zoom matching technology
IR light power	Auto adjusting
IR light model	Auto/Color/Black
Power	DC12V/3A
Protection Level	IP66
Cooling Structure	Dustproof structure outside the circle
Menu	Chinese/English
Work Environment	-35°C~65°C

Headquater: 401, Block G, 8# buliding, shangxue Industrial North Area, Bantian, Longgang District,Shenzhen, China
Email: care@santachi.net Web: www.santachi.net

Santachi® inspire the future

www.santachi.net