

SAN213200BAF

2.0 MP HD Day Night 4 in 1 Bullet Camera



1/2.7"



Day & Night



H.264



Automatic
White Balance



DC Power



IR Cut Filter



2.0 MP



Black/White
& Color



Weatherproof
IP66



- Supports AHD/TVI/CVI/CVBS Signals
- 2 megapixel (1080P) high resolution
- Max. 1920 × 1080 @25fps
- Lens 2.8 / 3.6 mm (6 mm/8 mm/12 mm Optional)
- Remote On Screen Display Setting
- H.264 Compression
- 3D Digital Noise Reduction
- IR range up to 20 m
- Power DC 12V
- IP66 Standard Weather Proof



SPECIFICATIONS:

Image Sensor	
Sensor size	1/2.7"
Effective Pixels	1920(H) x1080(V)
TV System	PAL/NTSC
Scanning System	Progressive
S/N Ratio	≥58db
IR Distance	20 m
IR On/Off Control	Auto/ Manual
IR LEDs	2 High Power Array LEDs

Lens			
Lens Type	Fixed		
Mount Type	Board-in		
Focal Length	(2.8, 3.6, 6, 8, 12 mm fixed)		
Max. Aperture	F1.2		
Optical Zoom	N/A		
Focus Control	Fixed		
Available lens	Lens	Angle (FOV)	Distance
Selected lens (by default)	2.8 mm	90	3 M
	3.6 mm	70	8 M
	6.0 mm	50	15 M
	8.0 mm	33	20 M
	12.0 mm	22	40 M

PTZ	
Pan/Tilt/Zoom	N/A
Pan/Tilt/Zoom Range	N/A
Auto Zoom	N/A
Auto Track	N/A

Intelligence	
IVS	N/A
Advanced Intelligent Functions	N/A

Video			
Video Output	AHD, TVI, CVI, CVBS		
Streaming Capability	2 Streams		
Resolution	1080P(1920×1080) /720P(1280×720) /960H D1(704×480)		
	CIF(352×240)		
Frame Rate	Main Stream: 2MP@(1 ~ 25fps)		
	Sub Stream: D1@(1 ~ 25fps) ;		
Bit Rate Control	CBR/VBR		
Bit Rate	maximum bitrate	minimum bitrate	ultra minimum bit rate
	2MP: 8192bps @ 25fps	512bps @25fps	D1: 95bps @1fps
Day/Night	Auto(ICR) ; Color; B/W		
BLC Mode	Off / On		
White Balance	Auto		
Auto Gain Control	Auto/Manual (level 1 to 100)		
DNR	1 to 15 levels		
Smart IR	Support		
Defog	Off / On (level 1 to 100)		
Digital Zoom	Manual		

Interface	
Video Interface	BNC
White Balance	ATW / MWB

Electrical	
Power Supply	DC 12V
Power Consumption	<11W

Environmental	
Operating Conditions	-10°C~+50°C (-4F ~ +122F) , Less than 95%RH (No condensation)
Storage Conditions	-20°C+50°C (-4F ~ +122F) , Less than 95%RH (No condensation)
Ingress Protection	IP66 Standard Weatherproof

Construction	
Casing	Metal + Plastic
Dimensions (Packed)	300 mm x 163 mm x 128 mm (Tolerance +/- 20mm)
Net Weight (Packed)	0.600kg (Tolerance +/- 0.20 kgs)