

SAN31400NSDB



4.0 MP H.265 Network Day & Night High Speed Dome Camera



Key Features

- Image Sensor: 1 / 3" CMOS
- Resolution: 4.0 MP
- Video Compression: H.265 / H.264
- Optical Zoom: 20x
- Focus Length: 4.7mm-94mm
- IR Distance: 150 meters
- Preset Points: 255
- Pan Range: 0°~360°
- Continue Tilt Range: 0°~93°
- Weather Proof Standard: IP66

SPECIFICATIONS:	
Sensor	1/3" CMOS
Effective pixels	2592x1944
Total pixel	Upto 5.0 Megapixels
Lens	20X optical zoom 4.7mm -94mm
Iris	F1.6~F2.8
Min.illumination	Color:0.5Lux B/W:0.05Lux IR ON:0Lux
D/N	IR Cut
WB	Manual/Auto
AGC	Manual/Auto
S/N Ratio	≥50dB
Communications Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,HTTPS,P2P
Software Control	IE, CMS, Management Platform
Mobile View(optional)	Support Android iPhone platform smartphone
Horizontal Rotation Speed	0.02-480°/S
Horizontal Rotation Range	360°continuous rotation
Tilt Rotation Speed	0.02-160°/S
Tilt Rotation Range	0°-93° auto flip 180°
Auto Control IR LED	PWM
A-B Scan	User programmable
A-B Scan Speed	1-64 levels setting available
Dwell Time	01-60s interval available
Preset Points	255
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
PWR On Action	Memory/Tour 1/360° scan/A-B scan/Preset 1-8/None
Park Time	1-60mins available
Communication Protocol	Pelco-D, Pelco-P, Samsung
Baud Rate	9600bps by default
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V 4A
IR Illumination Distance	150M
Power Consumption	≤ 25W
Lightning Protection	Transient voltage 6000V