

SAN61104DRZC



4 Channel AHD DVR



Key Features

- Multi Mode Switch
 - AHD: 4CH *20P
 - AHD+ANALOG: 2CH*720p+2CH*960H
 - Analog: 4CH*960H
- HDMI and VGA Output upto 1080P
- Record Resolution upto 720P
- 1* SATA (each port supports upto 4 TB)
- ONVIF Standard

Video & Audio Input	
Analog video input	4PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio Input	4PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)
Video & Audio Output	
HDMI Output	1024x768, 1280x720, 1280x1024, 1920x1080P
VGA Output	1024x768, 1280x720, 1280x1024, 1920x1080p
CVBS Output	1PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio Output	1PCS RCA Port(line level , impedance : 1kΩ)
Video & Audio Code and Decode Parameters	
Multi Mode Switch	AHD: 4CH*720P AHD+Analog: 2CH*720P+2CH*960H Analog: 4CH*960H
Video code resolution	960H/720P
Playback resolution	720P 60/72FPS or 720P 50/60FPS+D1 50/60FPS
Video frame rate	NTSC : 2~30FPS/S ; PAL : 2~25FPS/S
Video code rate	512Kbps/640kbps/768Kbps/1M/1.5M/2M/3M/4M
Audio compress standard	ADPCM
Audio code rate	16kpbs
Dual-stream	Yes
Hard Driver	
Mode	1*SATA
HDD Capacity	Each port support max 4TB HDD
External Port	
Voice Intercom	No
Internet Port	1PCS RJ45 10M / 100M adaptive Ethernet port
USB Port	2*USB2.0
Alarm Input	No
Alarm Output	No
Other	
Power Supply	DC12V
Power Consumption	≤12W
Work Temperature	-10°C~ +55 °C
Work Humidity	10%~90%
Net Weight (without HDD)	0.86kg (Tolerance ±100 gms)
Gross Weight (without HDD)	1.53kg (Tolerance ±100 gms)
Box size [L*W*H(cm)]	36 *27*8.5cm (Tolerance ±3cm)