

# SAN61205MDRZE



## 5CH AHD+IP Mobile DVR



### Key Features

- H.264 Compression, support 5CH (4CH HD/SDmixed + 1CH Network input)
- 3CH Video Output (2CH CVBS video, VGA output for optional)
- Realize real-time monitor through 3G/4G;
- Unique UPS Technology
- Support's HDD (2.5" Max 2TB) + 128GB SD Card Mirror Recording, protect DVR from shock & Dust damage
- Support HDD heating functions, can work in harsh environment.
- Show Car status/Plate/Driving Route/Low Speed/Over Speed information for convenient management
- Support Broadcast/Intercom/Text sent etc; can add oil sensor/temperature sensor/POS/LED Advertisement Panel
- Support IOS/Android Phone Remote monitoring

SPECIFICATIONS:	
Video compression	H.264 compression
OSD	Overlays information such as date time and vehicle ID
Resolution	1080P/720P/D1/HD1/CIF, MAX:4 channels 720P and 1 channels 1080P
Video Standard	PAL: 100ffs, CCIR625 line,60field; NTSC: 120ffs, CCIR525 line,60field; CIF: 256Kbps ~ 1.5Mbps, 8 level video quality optional; HD1: 600Kbps ~ 2.5Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional; 720P: 4Mbps-6Mbps, 8 levels video quality optional 1080P:
Preview	Support 1 channel and 5 channels preview, Support Manual/Alarm Trigger full screen preview
GPS Position	Support Built GPS/BD Module, can make playback analysis of vehicle routing
Smart Phone	Support Android / IOS Smart phone
Wireless Transmission	Support Built-in 3G/4G network, WCDMA, CDMA2000, TDD-LTE, FDD-LTE...
Video Input	04CH*720P AHD/SD/MIXED + 01CH*1080P Network ( Aviation connector) 1.0Vp-p 75Ω
Video Output	2CH CVBS+ VGA output for optional, 1.0Vp-p, 75 Ω, Aviation, Support 1CH Full Screen, 4CH Screen view
Image Quality	0-7 levels, 0 is the highest level.
Audio	Input: 4CH Aviation Plug Input + 1CH IPC input mixed Audio stream Output: 2CH headphone connect at front panel, BNC connect on Back panel
Storage Capacity	Max 2TB HDD supported ( Size: 2.5") Max 128GB SD Card Mirror Recording Keep Data Safety
Voice Call	Support voice call each other
Alarm	8CH Alarm Input,1CH AD Input, impulse speed input, Alarm Linkage 2CH Alarm Output, Support Light/Sound alarm sensor, Oil/Power cut off
USB Port	USB Interface on Front Panel, support USB flash disk upgrade to backup; hard disk box USB port, can back up video data
Communication Interface	3CH RS232, support extension device, such as POS machine, Oil Fuel sensor, LED advertising screen, etc. 2CH 485 interface, can connect PTZ, etc. 2CH CAN interface.
Playback	Max support 4CH Replay / Stop / Fast / Slow at same time; Support forward and backward play at the speed of x2, x4, x8, x16
Security	User / Admin 2 Level Different Password, support screen lock
Power Management	Adaptive wide power input, support Wide Voltage, Over-load, Over-voltage, Short Circuit, Reverse Protection. Support Time Setting/Delay power off
Voltage	Input: DC:+8V - +36V Output: +12V@2.5A, +5V@2.5A
Power	Working <5W
Temperature & Humidity	Temperature -20°C - +70°C, Humidity 20% - 80%
Size	200 (D) * 187 (W) * 62 (H) mm ( ± 20 mm) 1.90 KG ( ± 0.20 Kg)