

# SAN72132TRZC



1080P AHD / Network & 960H Analog 32 Channel Tribrid DVR



## Key Features

- 3 in 1 DVR/HVR/NVR features multi-mode input.
- Reliable cloud service
- H.264 High Profile compression algorithm.
- Supports full real-time encoding video, full real-time playback.
- Main stream and Sub-stream encoding.
- Support various mobile monitoring (iPhone, Windows Mobile, BlackBerry, Android)
- Powerful network services, easy to achieve interoperability.
- ONVIF Standard

## Specifications

### Video & Audio Input

Analog video input	32PCS BNC Port( Level: 1.0Vp-p, impedance : 75Ω)
Audio Input	16PCS RCA Port( Level : 2.0Vp-p, impedance : 1kΩ)

### Video & Audio Output

HDMI Output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
VGA Output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
CVBS Output	No
Audio Output	1PCS RCA Port( line level , impedance : 1kΩ)

### Video & Audio Code and Decode Parameters

Multi Mode Switch	AHD: 32CH*720P ; 24CH*720P ; 16CH*720P ; 16*960H ;
	AHD+IP: 4CH*720P( analog) + 4CH*720P( network) ;
	IP: 8CH*720P+1CH*1080P ; 4CH*1080P ; 20CH*960H ;
Video compress standard	H.264
Playback Quality	720P/960H/D1
Encode Ability	32CH*720P @12fps
Decode Ability	8CH*720P @12fps
Motion Detection	Each screen can be set to 192 ( 16 *12) detection areas;multi-levelsensitivitycan be set ( Limited localchannel)

### Record & Playback

Record mode	Manual>Alarm>Motion detection>Timing
Local Playback	8ch( local input mode)
Search Mode	Search by time, calendar, event, channel
Synchronously playback channels	1/4/8/9/16CH (It is defined with the mode switch)

### Hard Driver

Mode	2* SATA
HDD Capacity	Each port support max 6TB HDD

### External Port

Voice intercom	1PCS RCA Port( Level : 2.0Vp-p, impedance : 1kΩ)
Internet port	1PCS RJ45 10M / 100M adaptive Ethernet port
Serial port	1PCS RS485 Port; 1PCS RS232 Port;
USB port	2*USB2.0
Alarm	8 In / 1 Out (It is defined with the mode switch)

### Other

Power supply	DC12V
Power consumption	≤15W ( without HDD)
Work temperature	0°C- +55 °C
Work humidity	10%-90%
Box size [ W*L*H( cm) ]	48*34*10cm ( Tolerance ±3cm)