

# SAN72232TRZC



## 32 Channel 1080N Tribrid DVR



### Key Features

- 3 in 1 DVR/HVR/NVR features multi mode input.
- Reliable cloud service
- H.264 High Profile compression algorithm.
- Supports full real-time encoding video, full real-time playback.
- Main stream and Sub-stream encoding.
- Support various mobile monitoring (iPhone, Windows Mobile, BlackBerry, Android)
- Powerful network services, easy to achieve interoperability.
- ONVIF Standard

SPECIFICATIONS:	
Video & Audio Input	
Analog video input	32PCS BNC Port( Level: 1.0Vp-p, impedance : 75Ω)
Audio input	1PCS RCA Port( Level : 2.0Vp-p, impedance : 1kΩ)
Video & audio output	
HDMI output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
CVBS output	NO
VGA output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
Audio output	1PCS RCA Port( line level , impedance : 1kΩ)
Video & audio code and decode parameters	
Multi-mode switch	AHD: 32CH*1080N;24CH*1080N ; 16CH*1080N
	AHD+IP: 8CH*1080N ( analog) + 8CH*960P( network) ;
	IP: 32CH*1080P×16CH*3M×8CH*5M×
Video compress standard	H.264
Motion Detection	Each screen can be set to 192 ( 16 * 12) detection areas; multi-level sensitivity can be set ( Limited local channel)
Encode Ability	32CH*1080N @15fps
Decode Ability	8CH*1080N @15fps
Audio compress standard	G.711A
Record & Playback	
Record mode	manual>alarm>motion detection>timing
Local Playback	8ch( local input mode)
Searchmode	Search by time, calendar, event, channel
Synchronously playback channels	1/4/8/9/16CH (It is defined with the mode switch)
Storage & Backup	
Video storage	HDD, Network
Backup mode	Network, USB Hard disk, USB burner, SATA Burner
Hard driver	
Mode	2*SATA
HDD capacity	each port support max 6TB HDD
External port	
Voice intercom	1PCS RCA Port( Level : 2.0Vp-p, impedance : 1kΩ)
Internet port	1PCS RJ45 10M / 100M adaptive Ethernet port
Serial port	1PCS RS485 Port; 1PCS RS232 Port;
USB port	2*USB 2.0
Wireless	3G, WIFI ( Extended via USB)
Alarm input	16
Alarm output	4
System	
Operating System	embedded Linux
System resources	Simultaneously multi-channel real-time recording, playback, network operation, USB backup
Interface	
Operator Interface	Support 16-bit true color graphical menu interface and mouse operation
Preview	1/4/8/9/16/32
Other	
Power supply	DC12V/5A
Power consumption( without HDD)	≤15W
Work temperature	0°C~+55°C
Work humidity	10%~90%
Box Size ( W*L*H( cm ) )	48*34*10cm ( Tolerance +3cm)