

SAN72308TRZD



8 Channel 1080N Tribrid DVR



Key Features

- Multi Mode Switch
 - AHD: 8CH*1080N; 8CH*720P; 4CH*720P; 8CH*960H;
 - AHD+IP: 4CH*720P(analog) + 4CH*720P(network);
 - IP: 2CH*1080P + 2CH*720P; 8CH*720P ;
- HDMI and VGA Output upto 1080P
- 1* SATA (each port supports upto 6 TB)
- ONVIF Standard

Specifications

Video & Audio Input

Analog video input	8PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio Input	4PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)

Video & Audio Output

HDMI Output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
VGA Output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
CVBS Output	No
Audio Output	1PCS RCA Port(line level , impedance : 1kΩ)

Video & Audio Code and Decode Parameters

Multi Mode Switch (A is referred to analog and N is to Network)	AHD: 8CH*1080N; 8CH*720P; 4CH*720P; 8CH*960H; AHD+IP: 4CH*720P(analog) + 4CH*720P(network) ; IP: 2CH*1080P + 2CH*720P ; 8CH*720P ;
Video compress standard	H.264
Playback Quality	1080N/720P/960H
Motion Detection	Each screen canbe set to 192 (16 *12) detection areas;multi-level sensitivitycan be set (Limited localchannel)
Encode Ability	8CH*1080N / 8CH*720P
Decode Ability	4CH*1080N
Audio compress standard	G.711A

Record & Playback

Local Playback	4CH
Synchronously playback channels Dual-stream	1/4/8/CH (It is defined with the mode switch)

Hard Driver

Mode	1*SATA
HDD Capacity	Each port support max 6TB HDD

External Port

Serial port	1PCS RS485 Port; Support multiple PTZ protocols
Internet Port	1PCS RJ45 10M / 100M adaptive Ethernet port
USB Port	2*USB2.0
Alarm Input & Output	(OPTIONAL)
Alarm Output	(OPTIONAL)
Wireless	3G, WIFI (Extended via USB)

Other

Power Supply	DC12V 2A / 4A
Power Consumption	≤15W
Work Temperature	-0°C- +55 °C
Work Humidity	10%-90%
Box size [L*W*H(cm)]	34*26*9cm (Tolerance ±3cm)