

SAN72616TRZD



16 Channel 1080N Tribrid DVR



Key Features

- Multi Mode Switch
 - AHD: 16CH*1080N; 8CH*720P; 16CH*720P; 16CH*960H
 - AHD+IP: 4CH*720P(analog) + 4CH*720P(network); 8CH*720P(analog) + 8CH*720P(network);
 - IP: 1CH*1080P+8CH*720P; 4CH*1080P; 20CH*960H;
- HDMI and VGA Output upto 1080P
- 1* SATA (each port supports upto 6 TB)
- ONVIF Standard

Specifications

Video & Audio Input

| | |
|--------------------|--|
| Analog video input | 16PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω) |
| Audio Input | 2PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ) |

Video & Audio Output

| | |
|--------------|---|
| HDMI Output | 800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P |
| VGA Output | 800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P |
| CVBS Output | No |
| Audio Output | 1PCS RCA Port(line level , impedance : 1kΩ) |

Video & Audio Code and Decode Parameters

| | |
|---|---|
| Multi Mode Switch (A is referred to analog and N is to Network) | AHD: 16CH*1080N ; 08CH*720P ; 16CH*720P ; 16CH*960H AHD+IP: 4CH*720P(analog) + 4CH*720P(network) ; 8CH*720P(analog) + 8CH*720P(network) ; IP: 1CH*1080P+8CH*720P ; 4CH*1080P ; 20CH*960H ; |
| Video compress standard | H.264 |
| Playback Quality | 1080N/720P/960H |
| Motion Detection | Each screen can be set to 192 (16 *12) detection areas; multi-level sensitivity can be set (Limited local channel) |
| Encode Ability | 16CH*1080N @15fps / 16CH*720P |
| Decode Ability | 1CH*1080N @15fps / 1CH*720P |
| Audio compress standard | G.711A |

Record & Playback

| | |
|---|---|
| Local Playback | 4CH |
| Synchronously playback channels Dual-stream | 1/4/8/9/16CH (It is defined with the mode switch) |

Hard Driver

| | |
|--------------|-------------------------------|
| Mode | 1*SATA |
| HDD Capacity | Each port support max 6TB HDD |

External Port

| | |
|----------------------|---|
| Serial port | 1PCS RS485 Port; Support multiple PTZ protocols |
| Internet Port | 1PCS RJ45 10M / 100M adaptive Ethernet port |
| USB Port | 2*USB2.0 |
| Alarm Input & Output | No |
| Alarm Output | No |
| Wireless | 3G, WIFI (Extended via USB) |

Other

| | |
|--------------------------|-----------------------------|
| Power Supply | DC12V 2A / 4A |
| Power Consumption | ≤15W |
| Work Temperature | -0°C- +55 °C |
| Work Humidity | 10%-90% |
| Box size [L*W*H(cm)] | 34*26*9cm (Tolerance ±3cm) |