

SAN71120HRZB



20 Channel Embedded Hybrid DVR (16 Ch Analog + 4Ch Network)



Key Features

- 20 Ch. Hybrid Video Recorder
- 16Ch Analog and 4Ch Network Camera Input
- HDMI and VGA Output upto 1080P
- 1/4/9/16CH Synchronous Playback
- Record Resolution upto 720P
- 8Ch. Alarm Input
- 2* SATA (each port supports upto 3 TB)
- ONVIF Standard

Video & Audio Input	
Analog Video Input	16PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio Input	16PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)
Network Video Input	4CH
Video & Audio Output	
HDMI Output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
VGA Output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
CVBS Output	1PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio Output	1PCS RCA Port(line level , impedance : 1kΩ)
Video & Audio Code and Decode Parameters	
Record Resolution	CIF/HD1/D1/960H/720P
Motion Detection	Motion Detection Recording
Synchronously Playback Ch.	1/4/9/16CH
Record Management	
Record & Snapshot Mode	Manual, Regular, Motion, Alarm & Events Recording
Playback Mode	Regular, Alarm, Motion Detection & Events Playback
Backup Mode	Regular, Events & Manual Backup
Hard Driver	
Mode	2*SATA
HDD Capacity	Each port support max 3TB HDD
External Port	
Voice Intercom	No
Internet Port	1PCS RJ45 10M / 100M adaptive Ethernet port
USB Port	2*USB2.0
Alarm Input	8CH
Alarm Output	1CH
Network Management	
Network protocol	NTP, PPPoE, DDNS, FTP, ARSP, WIFI, 3G
Other	
Power Supply	DC12V
Power Consumption	≤18W
Work Temperature	-10°C~ +55 °C
Work Humidity	10%~90%
Net Weight (without HDD)	1.36kg (Tolerance ±100 gms)
Gross Weight (without HDD)	2.23kg (Tolerance ±100 gms)
Box size [L*W*H(cm)]	39*30*11cm (Tolerance ±3cm)