

SAN111500DAZ

5.0 MP HD (TVI Default) Day Night 4 in 1 CCTV Camera



1/2.5"



Day & Night




H.265/H.264



Automatic
White Balance



DC Power



IR Cut Filter



5.0 MP



Black/White
& Color



Weatherproof
IP65



- 5 megapixel High Resolution
- Max. 3072 × 1728 @20fps
- Lens 2.8 mm (3.6 mm/6 mm Optional)
- On-screen Display Function
- H.265/H.264 Compression
- 3D Digital Noise Reduction
- IR range up to 15 to 20 m
- Power DC 12V
- IP65 Standard Weather Proof



SPECIFICATIONS:	
Image Sensor	
Sensor size	1/2.5"
Effective Pixels	3027(H) x1728(V)
TV System	PAL/NTSC
Scanning System	Progressive
S/N Ratio	≥58db
IR Distance	20 m
IR On/Off Control	Auto/ Manual
IR LEDs	2 High Power Array LEDs

Lens			
Lens Type	Fixed		
Mount Type	Board-in		
Focal Length	(2.8, 3.6, 6 mm fixed)		
Max. Aperture	F1.2		
Optical Zoom	N/A		
Focus Control	Fixed		
Available lens	Lens	Angle (FOV)	Distance
Selected lens (by default)	2.8 mm	90	3 M
	3.6 mm	70	8 M
	6.0 mm	50	15 M

PTZ	
Pan/Tilt/Zoom	N/A
Pan/Tilt/Zoom Range	N/A
Auto Zoom	N/A
Auto Track	N/A

Intelligence	
IVS	N/A
Advanced Intelligent Functions	N/A

Video			
Video Output	AHD, TVI, CVI, CVBS		
Streaming Capability	2 Streams		
Resolution	5MP(20fps/12.5fps) /4MP(30/25/15) fps/1080P(30/25) fps		
	720P/960H/D1		
Frame Rate	Main Stream: 5MP@(1 ~ 20fps) / Sub Stream: D1@(1 ~ 25fps) ;		
Bit Rate Control	CBR/VBR		
Bit Rate	maximum bitrate	minimum bitrate	ultra minimum bit rate
	5MP: 3948bps @ 13fps	5MP: 789bps @ 13fps	D1: 34bps @1fps
Day/Night	Auto(ICR) ; Color; B/W,		
Brightness	1 to 20		
White Balance	ATW/MWB		
Exposure Mode	Globe/BLC/FLC		
Contrast	1 To 16		
Sharpness	1 To 16		
Color Gain	1 To 16		
DNR	1 To 16		
D-WDR	Off / On		
Mirror	H/V/HV/Default		
Digital Zoom	Manual		

Interface	
Video Interface	BNC
OSD / UTC	Available
White Balance	ATW

Electrical	
Power Supply	DC12V Power Consumption <11W

Environmental	
Operating Conditions	-10°C+50°C (-4F ~ +122F) ,Less than 95%RH (No condensation)
Operating Conditions	-20°C+50°C(-4F ~ +122F) ,Less than 95%RH (No condensation)
Ingress Protection	IP65 Standard

Construction	
Casing	Plastic
Dimensions (Packed)	132 mm x 132 mm x 115 mm (Tolerance +/- 20mm)
Net Weight (Packed)	0.25 kg (Tolerance +/- 0.15 kgs)