


SAN1160DPMS

6.0 MP IP Color Night Vision 2 Way Audio Camera



1/2.8" Sony
Image Sensor



6.0 Megapixel
Resolution



3.6 mm
Lens



IR Range
Upto 30 Mtr



H.265+
(Compatible with
H.265/H.264)



Audio
Communication



12VDC / PoE
Power Supply



IP50
Weather Proof



Reliable
Surveillance



- Image Sensor: 1 / 2.8" Sony
- Resolution: 6.0 Megapixel
- Lens: 3.6 mm
- IR Range: Upto 30 Mtr
- H.265+ (Compatible with H.265/H.264)
- Audio Communication
- Power: 12VDC / PoE
- Weather Proof Standard: IP50



SPECIFICATIONS:

System structure	Embedded RTOS,dual-core 32bit DSP(GK7205V300),pure hard compression ,watch dog
Sensor	6.0M 1/2.8" Black light illumination CMOS sensor,color 0.0001Lux@F1.2,black/white 0.0001Lux@F1.2
Video compression	H.265 +(Compatible with H.265/H.264) support dual stream,AVI;0.1M~8Mbps variable;1~30f/s variable
Image output	Main stream: 6MP 3072*2048@20fps; 5MP 2880*1616@25fps; 4MP 2560*1440@25fps; 2MP 1920*1080@25fps; sub-stream: 800*448@25fps
Shutter	1/50(1/60)s to 1/10,000s
Lens	3.6 mm
Day and night	Support IR-CUT coil has an internal resistance of 20 ohms, the power-on time is less than 200ma, and the voltage is 3.5V-6V
Noise reduction	Support 2D/3D
Wide dynamic	Support digital Wide dynamic
Auto iris	N/A
Audio compression	G.711,support bidirectional talk,audio&video synchronization
Audio interface	1ch input,level:2Vp-p,impedance:1kΩ,support sound pick-up input;1ch output,impedance:16Ω,30mw,support microphone
Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTPDHCP/NTP/UPnP etc
Reliability	Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing
Intelligence analysis	<input type="checkbox"/> Supporting human detection, face detection, Vehicle shape detection and support to customize other intelligent functions
Other function	Support WEB,OSD,live video transmission,motion detect and IO alarm,front-end storage/playback/download, and center reminder and image linkage,support JPEG capture; united remote client monitoring software、MYEYE,perfect SDK;
ONVIF	Support
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
Power	DC12V/2A input, power consumption:≤3W,