

SAN2140M

4.0 MP WIFI IP Camera



4.0 MP HD Resolution



Humanoid Detection



Dual Light Day & Night



SD Card Slot Up to 128GB



ICR Day & Night Monitoring



IP66 Weatherproof



Digital WDR & 3D Noise Reduction



3D Noise Reduction



Mobile Remote Monitoring (iOS, Android)



- 4.0 MP 1/3" high performance CMOS sensors;
- HD resolution, the image is clear and delicate;
- Support humanoid, intelligent functions (crossing-line detection, area detection, etc.);
- Multiple modes such as dual light alert, full color day and night, infrared night vision can be switched smoothly;
- External storage SD card slot, up to 128GB;
- ICR automatic switching to realize day and night monitoring;
- Comply with IP66 weatherproof design;
- Support digital wide dynamic, 3D noise reduction function;
- Support mobile phone remote monitoring (iOS, Android);



SPECIFICATIONS:

Module	
System structure	Embedded RTOS,dual-core 32bit DSP, pure hard compression, watch dog
Sensor	4.0 MP 1/3" AI back light CMOS sensor, color 0.0001Lux@F1.2, black/white 0.0001Lux@F1.2
Video compression	H.265AI(Compatible with H.265/H.264), support dual stream, AVI;0.1M~10Mbps variable;1~30f/s variable
Image output	Main stream: 2560*1440@25fps,2304*1296@25fps,1920*1080@25fps;sub-stream: 800*448@25fps;
Shutter	1/50(1/60) s to 1/10,000s
Lens	3.6 mm
Image	
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Auto iris	N/A
Interface	
Audio compression	G.711, support bidirectional talk, audio & video synchronization
Audio interface	1 input, MIC: Selection range -28dB~-36dB, -33dB is recommended. 1 Output, Speaker: 8Ω2W is recommended.
Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/DHCP/NTP/UPnP etc
Extension interface	SD card slot,WIFI
Singal interface	One IR-CUT interface
Reset interface	Support
SD Card	supports 8-128GB
Intelligence	
Intelligence analysis	Supporting Human shape detection, face detection, face capture, license plate recognition, passenger flow statistics, and support to customize other intelligent functions
Other function	
Other function	Support WEB,OSD,live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support FTP capture;united remote client monitoring software、MYEYE;perfect SDK;
ONVIF	Support
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
General	
Reliability	Comprehensive lightning protection, 7 * 24 hours -10°C~65°C high temperature stable and reliable testing
Power	DC12V/2A input, power consumption: ≤3W
Other	Support POE power supply