

SAN2150BPMS

5.0 MP IP Color Night Vision 2 Way Audio Camera



1/3" CMOS
Image Sensor



5.0 Megapixel
Resolution



3.6 mm
Lens



IR Range
Upto 30 Mtr



H.265AI
(Compatible with H.265/H.264)



Audio
Communication



12VDC / PoE
Power Supply



IP66
Weather Proof



Reliable
Surveillance



- Image Sensor: 1 / 3" CMOS
- Resolution: 5.0 Megapixel
- Lens: 3.6 mm
- IR Range: Upto 30 Mtr
- H.265AI(Compatible with H.265/H.264)
- Audio Communication
- Power: 12VDC / PoE
- Weather Proof Standard: IP66



SPECIFICATIONS:

Module	
System structure	Embedded RTOS,dual-core 32bit DSP,pure hard compression ,watch dog
Sensor	1/3" black light CMOS sensor, color 0.0001Lux@F1.2, black/white 0.0001Lux@F1.2
Video compression	H.265AI(Compatible with H.265/H.264), support dual stream, AVI;0.1M~10Mbps variable;1~30f/s variable
Image output	Main stream: 2880*1616@20fps,2560*1440@20fps,2304*1296@25fps,1920*1080@25fps ;
	sub-stream: 800*448@25fps;
Shutter	1/50(1/60) s to 1/10,000s
Day and night	Support IR-CUT, IR-CUT coil has an internal resistance of 20 ohms, the power-on time is less than 200ma, Recommended use: 5V standard voltage IR-CUT
Lens	
Lens	3.6 mm
Image	
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Auto iris	N/A
Interface	
Audio compression	G.711, support bidirectional talk,audio&video synchronization
Audio interface	1 input, MIC: Selection range -28dB~-36dB, -33dB is recommended.
	1 Output, Speaker: 8Ω2W is recommended.
Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTPDPHCP/NTP/UPnP etc
Reset interface	Support
Intelligence	
Intelligence analysis	Supports human shape detection, facial detection, vehicle shape detection, and customization of other intelligent functions
Other function	
Other function	Support WEB,OSD,live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support FTP capture ; united remote client monitoring software、MYEYE;perfect SDK;
ONVIF	Support
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
General	
Reliability	Comprehensive lightning protection, 7 * 24 hours -10°C~65°C high temperature stable and reliable testing
Power	DC12V/2A input, power consumption: ≤3W
Other	Support POE power supply