


# SAN2160BPMS

## 6.0 MP IP Color Night Vision 2 Way Audio Camera



1/2.8" Sony  
Image Sensor



6.0 Megapixel  
Resolution



3.6 mm  
Lens



30M  
IR Range  
Upto 30 Mtr



H.265+  
(Compatible with  
H.265/H.264)



Audio  
Communication



12VDC / PoE  
Power Supply



IP66  
Weather Proof



Reliable  
Surveillance



- Image Sensor: 1 / 2.8" Sony
- Resolution: 6.0 Megapixel
- Lens: 3.6 mm
- IR Range: Upto 30 Mtr
- H.265+ (Compatible with H.265/H.264)
- Audio Communication
- Power: 12VDC / PoE
- Weather Proof Standard: IP66



**SPECIFICATIONS:**

System structure	Embedded RTOS,dual-core 32bit DSP(GK7205V300),pure hard compression ,watch dog
Sensor	6.0M 1/2.8" Black light illumination CMOS sensor,color 0.0001Lux@F1.2,black/white 0.0001Lux@F1.2
Video compression	H.265 +(Compatible with H.265/H.264) support dual stream,AVI;0.1M~8Mbps variable;1~30f/s variable
Image output	Main stream: 6MP 3072*2048@20fps; 5MP 2880*1616@25fps; 4MP 2560*1440@25fps; 2MP 1920*1080@25fps; sub-stream: 800*448@25fps
Shutter	1/50(1/60)s to 1/10,000s
Lens	3.6 mm
Day and night	Support IR-CUT coil has an internal resistance of 20 ohms, the power-on time is less than 200ma, and the voltage is 3.5V-6V
Noise reduction	Support 2D/3D
Wide dynamic	Support digital Wide dynamic
Auto iris	N/A
Audio compression	G.711,support bidirectional talk,audio&video synchronization
Audio interface	1ch input,level:2Vp-p,impedance:1kΩ,support sound pick-up input;1ch output,impedance:16Ω,30mw,support microphone
Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTPDHCP/NTP/UPnP etc
Reliability	Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing
Intelligence analysis	Supporting human detection, face detection, Vehicle shape detection and support to customize other intelligent functions
Other function	Support WEB,OSD,live video transmission,motion detect and IO alarm,front-end storage/playback/download, and center reminder and image linkage,support JPEG capture; united remote client monitoring software、MYEYE;perfect SDK;
ONVIF	Support
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
Power	DC12V/2A input, power consumption:≤3W,