

SAN323030DLPTZ

3.0 MP + 3.0 MP Dual Lens 50x PTZ Camera



4.5-inch Zoom Dome
Metal & ABS Design



Mobile Remote
Capture & Playback



3MP Bullet + 3MP Dome
= 6MP Ultra Clear



50X
Optical Zoom



Dual Laser Night Vision
Color 60m / IR 120m



PTZ Rotation
0-355° / 0-90°



16 Preset Points Cruise
2-Point Scan & Guard



ONVIF & Hikvision Protocol
Compatible with NVRs



AI Human Detection
Smart Full-Color Night Vision



- 4.5-inch zoom dome camera, metal front cover & ABS upper cover, light in size.
- Mobile phone remote: image capture, remote video playback.
- 3 million bullet camera & 3 million dome camera, the upper and down pictures are combined into one 6 million picture. The picture is clear and delicate.
- 50X optical zoom
- Using high-power dual laser night vision lights, full-color night vision 60 meters, infrared night vision 120 meters.
- PTZ rotation, horizontal 0-355°, vertical 0-90°, rotation speed 0-20°/s.
- Support 16 preset points cruise, support two-point scanning, watching guard, power-off memory.
- Comes with ONVIF protocol and Hikvision protocol, compatible with Hikvision, Dahua and other mainstream NVRs.
- Support AI human detection, full-color day and night, black and white by default, automatically turn on color vision if someone enters at night
- Built-in TF card storage, maximum support 128GB; support cloud storage.
- Comes with a 15-meter voice-pickup function, and a built-in subwoofer for 40-meter two-way audio.
- Built-in horn, optional voice alarm: Someone enter the monitoring area, the siren will alarm.
- Support 2.4G WiFi, the wireless connected distance is about 30 meters;
- Working temperature: -20°C~60°C; IP65 waterproof, support indoor and outdoor installation.

SPECIFICATIONS:	
Master Control	Dual-core 32-bit DSP, pure hard compression, watchdog
Sensor	Three 3 million 1/2.8" AI high-performance CMOS sensors
Minimum Illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter	1/50(1/60)S-1/10000S
Lens	F1.4*3.6MM+Ultra-high-definition 50X zoom
Noise Reduction	Support 2D/3D noise reduction
Video Format	H.265AI
Resolution	Main resolution: 2304*2592; Sub-resolution: 800 * 896
Frame Rate	12 fps
Intelligent Analysis	Support human shape detection
Reset Point Cruise	Support 16 preset points cruise, support two-point scanning, watching guard, power-off memory.
PTZ Rotation	Horizontal 0-355°, vertical 0-90°, rotation speed 0-20°/s.
Light Source	4*K1 high-power white lights + 6*K1 high-power infrared lights + 2*K1 laser lights on the down dome camera; 5*4 mixed light angle design on the upper bullet camera
Light Mode	Starlight full color/infrared night vision/dual lights warning
Two-way Voice	Support
Cloud Storage	Support
Protocol	Support NETIP and ONVIF protocol
Network Interface	10M/100M adaptive Ethernet port
Storage Interface	Local TF card (up to 128GB)
Reset Key	Support one-click reset
Wireless Standard	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Power Consumption	20W
Weight	1.4KG
Working Temperature	-20 ° C -60 ° C, humidity less than 90% [no condensation]
Power Supply	DC 12V 2A